



LEFT SIDE VIEW

FRONT VIEW

NOTES:

- A. SIDEWALK BARRICADES TO BE ERECTED AT EACH LOCATION WHERE SATISFACTORY PROVISION CANNOT BE MADE FOR PEDESTRIANS TO CONTINUE BEYOND THE TERMINUS OF A SIDEWALK.
- B. ALL EXPOSED BARRICADE SURFACES TO BE PRIMED AND PAINTED WITH TWO (2) COATS OF WHITE PAINT CONFORMING TO SECTION 91-3.01 AND 91-3.02 OF THE STATE STANDARD SPECIFICATIONS.
- C. BOTTOM RAIL TO BE LOCATED NO HIGHER THAN 5" ABOVE ADJACENT PEDESTRIAN ACCESSIBLE ROUTE FINISHED SURFACE.

①	2" x 6" REDWOOD (TYP)
②	4" x 4" x 5'-6" MIN PRESSURE TREATED DOUGLAS FIR OR REDWOOD POSTS (TYP)
③	½" CARRIAGE BOLTS WITH WASHERS AND NUTS (TYP)

THE CITY OF WEST SACRAMENTO - STANDARD DETAIL



STANDARD
DETAIL #
242

TITLE:

SIDEWALK BARRICADE

